



Logypal è un prodotto di Imball Nord Srl
Sede legale: viale Felice Cavallotti, 10 - 35124 Padova
Imball Nord: Via dell'Artigianato, 12 Z.A. - 30030 Tombelle di Vigonovo (VE)
Tel. +39 049 9800857 / Fax +39 049 9801455 / info@logypal.com / www. logypal.com

Data Sheet

1000x1200 Logypal





Technical data	cod. LOGYPAL2	cod. LOGYPAL2 + cod. LOGYPALKIT
Dimension mm (L x W x P)	1200x1000x145	1200x1000x148
Height mm	145	148
Pallet entry height mm	108	111
Height topdeck mm	38	38
Weight kg (+/- 5%)	7,20	8,90
Dinamic loading kg*	750	950
Static loading kg*	1500	1900
Nestable	Yes	No
Number of pallet for stack	52	18
Height of stack of pallet mm	2520	2660
Stacking weight kg	375	160
Number of pallet for truck load (mt. 13,60)	1352	468
RFID ready	Yes	Yes
Material	Polypropylene recycled	Polypropylene recycled
Temperature range	-20°C to +60°C	-20°C to +60°C
Standard color (any color on demand)	Gray	Gray

^{*} depending upon type of loading.

Guidelines values were performed in accordance with ISO 8611-1: 2011. We recommend you always check your load conditions and pallet storage, considering environmental factors such as the storage time and the storage area temperature. Imball Nord Srl reserves the right to change any of the stated information without prior notice. Logypal is non FDA. Use with barrier materials for direct food contact.