



Logypal è un prodotto di Imball Nord Srl
Sede legale: viale Felice Cavallotti, 10 - 35124 Padova
Imball Nord: Via dell'Artigianato, 12 Z.A. - 30030 Tombelle di Vigonovo (VE)
Tel. +39 049 9800857 / Fax +39 049 9801455 / info@logypal.com / www. logypal.com

Data Sheet

800x1200 Logylight



Technical data	cod. LOGYPAL3	cod. LOGYPAL3 + cod. LOGYPALKIT
Dimension mm (L x W x H)	1200x800x130	1200x800x133
Height mm	130	133
Pallet entry height mm	104	107
Height topdeck mm	27	27
Weight kg (+/- 5%)	3,10	4,80
Dinamic loading* kg	200	250
Static loading* kg	600	750
Nestable	Yes	No
Number of pallet for stack	72	19
Height of stack of pallet mm	2613	2527
Stacking weight kg	227	92
Number of pallet for truck load (mt. 13,60)	2376	627
RFID ready	NO	NO
Material	Recycled Polypropylene	Recycled Polypropylene
Temperature range	-20°C +60°C	-20°C +60°C
Standard color (any color on demand)	Grey	Grey

^{*} depending upon type of loading

We did the test as ISO 8611-1:2011. We warn to check always the conditions of load and of storage of the pallet, taking into account the environmental factors like the time of storage and the temperature of the warehouse. Imball Nord s.r.l. can modify the technical characteristics that we have described in the upper part whenever it likes, without forewarning.

You can't put the pallets in direct contact to the food; you must to use something amid the food and the pallet.